
CABLE S-VGA-XGA 5X0.08 (75) + 5X0.08 BLACK 100MT

Special 75Ohm video cable
For VGA and XGA
applications

Reference: C146



Black flame retardant soft PVC.
External diameter 9.00 (ñ 0.20) mm.
O.F.C. O.F.C. tinned copper braid shield, 80% coverage + drain wire.
Grouping with non-woven polyester tape.
Coaxial video:
PVC sheath. Colored: Red, Green, Blue, White, Black.
Diam. 2.40 (ñ 0.20) mm.
O.F.C. tinned copper spiral shield, 100% coverage.
PPE insulated. Diam.1,40 (ñ 0,20) mm.
Tinned copper strands O.F.C. 7x0.12 mm.
Nominal section 5x0.08 mmý (75Ohm).
Isolated nuclei:
PVC sheath. Colored: White, brown, red, orange, yellow.
Diam.0.90 (ñ 0.20) mm.
O.F.C. tinned copper strand formation 7x0.12 mm.
Nom. Section 5x0.08 mmý.
Ownership:
Conductors Resistance 203 Ohm / Km
Impedence 75 Ohm
Velocity of Propagation 66%
Capacity Core / Shield 67 pF / m
Operating temperatures -20 / + 70 ø C
Attenuation dB / 100 m:
50 MHz 19.70
100 MHz 28.70
200 MHz 42.00
400 MHz 61.20
800 MHz 88.50
1000 MHz 105.00
RoHS3 Compliant: Ver. A / 16.05.17