

---

# VGA CABLE 3X0.08 (75) + 7X0.08 GRAY 100MT

Special video cable -  
3x75Ohm + 7x0.08 mm  
For making VGA and XGA  
cables.

Reference: C258



Gray soft flame retardant PVC.  
External diameter 7.60 (ñ 0.20) mm.  
O.F.C. O.F.C. tinned copper braid shield, 80% coverage + drain wire.  
Grouping with non-woven polyester tape.  
3x HD Coax Video:  
105 ø HT PVC sheath - Colored: Red, Green and Blue.  
Diam. 2.40 (ñ 0.20) mm.  
O.F.C. O.F.C. tinned copper spiral shield, 100% coverage.  
PPE insulated. Diam.1,40 (ñ 0,20) mm.  
Tinned copper strands O.F.C. 7x0.12 mm.  
Nominal section 3x0.08 mmý (75Ohm).  
7x Isolated nuclei:  
Sheath in PVC HT 105 ø - Colored: White, Brown, Red, Orange, Yellow,  
Green Black. Diam.0.90 (ñ 0.20) mm.  
O.F.C. tinned copper strand 7x0.12 mm.  
Nominal section 7x0.08 mmý.  
Ownership:  
Conductors Resistance 203 Ohm / Km  
Impedence 75 Ohm  
Velocity of Propagation 66%  
Capacity Core / Shield 67 pF / m  
Operating temperatures -20 / + 70 ø C  
Attenuation dB / 100 m:  
50 MHz 19.70  
100 MHz 28.70  
200 MHz 42.00  
400 MHz 61.20  
800 MHz 88.50  
1000 MHz 105.00  
RoHS2 Compliant: Ver. A / 16.05.17