

---

# CABLE FOR SPEAKERS 4X2,50 + 4X4,00 BLACK 100 MT

Flexible cable for speakers -  
4x2.50 + 4x4.00 mm<sup>2</sup> -  
BLACK color  
For the wiring of professional  
speakers and pre-made  
cables

Reference: C289/NE



Soft PVC sheath. - available in different colors.

External cable Diam.16.50 (ñ 0.20) mm.

Core insulation with PVC sheath.

The 4x2.50 mm<sup>2</sup> section cores have diam. 3.50 (ñ 0.20) mm. and are colored in red, light blue, blue and green.

The cores section 4x4.00 mm<sup>2</sup> have diam. 4.20 (ñ 0.20) mm.

and are colored in yellow, gray, brown and orange.

All conductors are in O.F.C.

The conductors with a cross-section of 4x2.50 mm<sup>2</sup> have a stranded formation of 80x0.20 mm. The conductors with a section of 4x4.00 mm<sup>2</sup> have a 128x0.20 mm strand formation.

Ownership:

Section 2.50 mm<sup>2</sup> Conductor resistance: 6.41 Ohm / Km

Sect. 4.00 mm<sup>2</sup> Conductor resistance: 4.31 Ohm / Km

Maximum rated voltage: 49V

Operating temperature: -15 / + 70 ° C

RoHS2 Compliant: Ver. A / 16.05.17