
MULTICOAXIAL VIDEO CABLE 5X0.08 (75) BLACK 100MT

Multi Mini special coaxial
video cable - 5x0.08 mm (75
Ohm)

For applications in video
transmission systems and
professional monitors.

Reference: C145



Black fireproof PVC sheath. External diameter 9,20 (ñ 0,20) mm.

Grouping with non-woven polyester tape.

Soft PVC sheath on single conductors. Diam. 2.40 (ñ 0.20) mm.

Colorful: Red, Green, Blue, Black and White.

O.F.C. tinned copper braid shield which covers 90%.

Core insulation with PPE - Diam. 1.40 (ñ 0.20) mm.

O.F.C. tinned copper braid formation, 7x0.12 mm.

Nom. Section 5x0.08 mm² (75Ohm).

Ownership:

Conductor resistance 203 Ohm / Km

Core / Screen Capacity 67 pF / mt

Propagation speed 66%

Impedance 75 Ohm

Maximum rated voltage 49 V

Operating temperature -20 / + 70 °C

Attenuation dB / 100 mt:

50 MHz 19.70

100 MHz 28.70

200 MHz 42.00

400 MHz 61.20

800 MHz 88.50

1000 MHz 105.00

RoHS3 Compliant: Ver. A / 07.12.2015