

---

# CABLE S-VGA-XGA 5X0.08 (75) + 5X0.08 BLACK 100MT

Special 75Ohm video cable  
For VGA and XGA  
applications

Reference: C146



Black flame retardant soft PVC.  
External diameter 9.00 (ñ 0.20) mm.  
O.F.C. O.F.C. tinned copper braid shield, 80% coverage + drain wire.  
Grouping with non-woven polyester tape.  
Coaxial video:  
PVC sheath. Colored: Red, Green, Blue, White, Black.  
Diam. 2.40 (ñ 0.20) mm.  
O.F.C. tinned copper spiral shield, 100% coverage.  
PPE insulated. Diam.1,40 (ñ 0,20) mm.  
Tinned copper strands O.F.C. 7x0.12 mm.  
Nominal section 5x0.08 mmý (75Ohm).  
Isolated nuclei:  
PVC sheath. Colored: White, brown, red, orange, yellow.  
Diam.0.90 (ñ 0.20) mm.  
O.F.C. tinned copper strand formation 7x0.12 mm.  
Nom. Section 5x0.08 mmý.  
Ownership:  
Conductors Resistance 203 Ohm / Km  
Impedence 75 Ohm  
Velocity of Propagation 66%  
Capacity Core / Shield 67 pF / m  
Operating temperatures -20 / + 70 ø C  
Attenuation dB / 100 m:  
50 MHz 19.70  
100 MHz 28.70  
200 MHz 42.00  
400 MHz 61.20  
800 MHz 88.50  
1000 MHz 105.00  
RoHS3 Compliant: Ver. A / 16.05.17