


---

# KOMBY CABLE -1 VIDEO + SWITCH 1X0.26 (75) + 2X0.50 WHITE 100 MT

Special video cable -  
1x75Ohm + 2x0.50mm  
For general video and video  
surveillance applications.

Reference: C227



White fireproof soft PVC sheath.  
External cable Dimensions 8.00 (ñ 0.20) mm.  
75 Ohm Video  
White fireproof PVC sheath.  
Diameter 4.10 (ñ 0.20) mm.  
O.F.C.red copper braid shield Coverage 85%.  
White PPE insulation. Diameter 2.70 (ñ 0.20) mm.  
O.F.C. red copper red rigid wire formation 1x0.58 mm.  
Nom. Section 1x0.26 mm<sup>2</sup>  
Isolated nuclei  
Sheaths in fireproof PVC. Colored one black and one red.  
Diameter 2.10 (ñ 0.20) mm.  
16x0.20 mm strand formation in OFC red copper.  
Nom. Section 2x0.50 mm<sup>2</sup>.  
Ownership:  
Free Conductors Resistance 38 Ohm / Km  
Coax Conductor Resistance 75 Ohm / Km  
Coax Capacity Core / Shield 67 pF / mt  
Coax Impedance 75 Ohm  
Max Rated Voltage 49V  
Operating temperatures -20 / + 70 °C  
Attenuation dB / 100 m:  
50 MHz 17.2  
100 MHz 24.6  
200 MHz 33.7  
400 MHz 40.5  
800 MHz 65.5  
1000 MHz 87.2