
MULTICOAXIAL CABLE -VIDEO + SWITCH 5X0.08 (75) + 4X0.22 BLACK 100 MT

Super special 75Ohm video
cable

APPLICATIONS RGB video +
command / switch

Reference: C263SUPER



Gray soft flame retardant PVC.

External diameter 10.00 (ñ 0.20) mm.

5x Coax Video:

PVC sheath. Colored: Red, Green, Blue, Black, White.

Diam. 2.80 (ñ 0.20) mm.

O.F.C. tinned copper spiral shield, 100% coverage.

PEE insulated. Diam. 1.60 (ñ 0.20) mm.

Tinned copper strands O.F.C. 10x0.10 mm.

Nominal section 5x0.08 mm² (75Ohm).

4x Isolated nuclei:

PVC sheath. Colored: Yellow, Brown, Gray, Purple.

Diam. 1.20 (ñ 0.20) mm.

O.F.C. tinned copper strand formation 7x0.20 mm.

Nominal section 4x0.22 mm².

Ownership:

Coax Conductors Resistance 203 Ohm / Km

Impedence 75 Ohm

Velocity of Propagation 66%

Capacity Core / Shield 67 pF / m

Free Conductors Resistance 79.15 Ohm / Km

Operating temperatures -20 / + 70 °C

Attenuation dB / 100 m:

50 MHz 19.50

100 MHz 28.50

200 MHz 41.70

400 MHz 60.20

800 MHz 87.30

1000 MHz 103.00

RoHS2 Compliant: Ver. A / 16.05.17