

---

# DIGITAL DMX AUDIO CABLE - PUR 2X0.35 BLACK 100 MT

DMX Digital Audio cable 110  
Ohm AES / EBU - 2x0.35 mm  
- BLACK color

For outdoor use with  
polyurethane sheath.

APPLICATIONS Digital audio  
applications and DMX Light

Reference: TSK1038PUR



Black PUR sheath. External diameter. 6,10 (ñ 0,20) mm. External use.  
Flame retardant, halogen free and resistant to UV, chemical, oil and water.  
O.F.C. Opaque tinned copper 85% + O.F.C. tinned  
Copper drain wire.  
Waste filler between conductors and total non-woven polyester taping.  
Core insulation with PPE, colored one red and one blue.  
Diam. 1.60 mm (ñ 0.20) mm.  
Formation of tinned copper O.F.C. 11x0.20 mm.  
Nom. Section 2x0.35 mm<sup>2</sup>.  
Ownership:  
Conductor resistance 58.00 Ohm / Km  
Core / Core capacity 55 pF / m  
Core / Shield capacity 62 pF / m  
Impedance 110 Ohm  
Maximum rated voltage 49 V  
Operating temperature -40 / + 80 °C  
RoHS3 Compliant: Ver. B / 29.04.19