
DIGITAL CABLE DMX AUDIO + POWER 1X2X0,22 + 3X0,75 BLACK 100 MT

Special DMX cable 110 Ohm
- 1x2x0.22 + 3x0.75 mm
APPLICATIONS Active digital
audio cables (PHONO /
NETWORK)

Reference: TSK1048



Black fireproof PVC sheath.

External cable Diam.10,00 (ñ 0,20) mm.

The Digital Audio pair and the three power conductors are twisted together with filler and wrapped with non-woven polyester tape.

Digital Audio Pair 110 Ohm:

Black fireproof PVC sheath. Diam.4.30 (ñ 0.20) mm.

O.F.C. red copper 100% spiral cover + O.F.C. tinned copper

Drain wire.

Core insulation with PPE, colored one red and one blue.

Diam. 1.50 (ñ 0.20) mm.

Tinned copper O.F.C. - formation 28x0,10 mm.

Nom. Section 2x0.22 mm².

Power conductors:

Core insulation with, flame retardant PVC sheath, brown color,

Blue and yellow / green - Diam. 2,10 (ñ 0,20) mm.

H: Red copper O.F.C. - formation 24x0.20 mm.

Nom. Cross section 3x0.75 mm².

Ownership:

Resistance of digital audio cables 79.15 Ohm / Km

Power conductor resistance 21.93 Ohm / Km

Core / Core capacity 50 pF / mt

Core / Shield capacity 95 pF / mt

Maximum rated voltage 49 V

Impedance 110 Ohm

Operating temperature -20 / + 70 °C

RoHS2 Compliant: Ver. A / 16.05.16