DIGITAL CABLE DMX AUDIO + POWER 1X2X0,22 + 3X0,75 BLACK 100 MT



Special DMX cable 110 Ohm - 1x2x0.22 + 3x0.75 mm APPLICATIONS Active digital audio cables (PHONO / NETWORK)

Reference: TSK1048

Black fireproof PVC sheath.
External cable Diam.10,00 (ñ 0,20) mm.
The Digital Audio pair and the three power conductors are twisted together with filler and wrapped with non-woven polyester tape.
Digital Audio Pair 110 Ohm:
Black fireproof PVC sheath. Diam.4.30 (ñ 0.20) mm.
O.F.C. red copper 100% spiral cover + O.F.C. tinned copper
Drain wire.
Core insulation with PPE, colored one red and one blue.
Diam. 1.50 (ñ 0.20) mm.
Tinned copper O.F.C. - formation 28x0,10 mm.
Nom. Section 2x0.22 mmý.
Power conductors:
Core insulation with, flame retardant PVC sheath, brown color,
Blue and yellow / green - Diam. 2,10 (ñ 0,20) mm.
H: Red copper O.F.C. - formation 24x0.20 mm.
Nom. Cross section 3x0.75 mmý.
Ownership:
Resistance of digital audio cables 79.15 Ohm / Km
Power conductor resistance 21.93 Ohm / Km
Core / Core capacity 50 pF / mt
Core / Shield capacity 95 pF / mt
Maximum rated voltage 49 V
Impedance 110 Ohm
Operating temperature -20 / + 70 ø C
RoHS2 Compliant: Ver. A / 16.05.16