
COAX HDTV - HD SDI CABLE 23 AWG Ø 4.0 MM BLACK 100 MT

HD SDI - 75 Ohm coaxial
cable - 1x0.28 mm
APPLICATIONS Digital video
for high definition video
transmission and installation

Reference: TSK1077LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.
Limited application outside. External diameter. 4.20 (ñ 0.20) mm.
First O.F.C. tinned copper covering 95% of the braid.
Second shield in aluminum tape, 100% coverage.
Core insulation with PE foam. Diam. 2.80 (ñ 0.20) mm.
Formation of rigid wire 1x0.60 mm in red copper O.F.C.
Nom. Section 1x0.26 mm².
Ownership:
Conductor resistance 62 Ohm / Km
Core / Screen Capacity 53.5 pF / m.
Propagation speed 82%
Impedance 75 Ohm
Nom. Delay 4.0 ns / m.
Operating temperature -30 / + 70 °C
Attenuation dB / 100m:
10 MHz 3.31
100 MHz 11.80
1000 MHz 38.07
2000 MHz 54.48
3000 MHz 69.47
4500 MHz 88.89
RoHS2 Compliant: Ver. A / 16.05.16