
COAX HDTV - HD SDI CABLE 20 AWG Ø 5.9 MM BLACK 100 MT

HD SDI - 75 Ohm coaxial
cable - 1x0.52 mm
APPLICATIONS Digital video
for high definition video
transmission and installation

Reference: TSK1078LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.
Limited application outside. External diameter. 6.00 (ñ 0.20) mm.
First O.F.C. tinned copper covering 95% of the braid.
Second shield in aluminum tape, 100% coverage.
Core insulation with PE foam. Diam. 3.50 (ñ 0.20) mm.
Formation of rigid wire 1x0.80 mm in red copper O.F.C.
Nom. Section 1x0.50 mm².
Ownership:
Conductor resistance 38 Ohm / Km
Core / Screen Capacity 53.5 pF / m.
Propagation speed 82%
Impedance 75 Ohm
Nom. Delay 4.0 ns / m.
Operating temperature -30 / + 70 °C
Attenuation dB / 100m:
10 MHz 2.03
100 MHz 7.31
1000 MHz 24.60
2000 MHz 36.74
3000 MHz 50.11
4500 MHz 67.64
RoHS2 Compliant: Ver. A / 16.05.16