
COAX HDTV - HD SDI CABLE 18 AWG Ø 7.0 MM BLACK 100 MT

3G - SDI - 75 Ohm coaxial
cable - 1x0.80 mm
APPLICATIONS Digital video
for high definition video
transmission and installation

Reference: TSK1079LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.
Limited application outside. External diameter. 7.00 (ñ 0.20) mm.
First O.F.C. tinned copper covering 95% of the braid.
Second shield in aluminum tape, 100% coverage.
Core insulation with PE foam. Diam. 4.60 (ñ 0.20) mm.
Formation of rigid wire 1x1,00 mm in red copper O.F.C.
Nom. Section 1x0.80 mm².
Ownership:
Conductor resistance 21 Ohm / Km
Core / Screen Capacity 53.5 pF / m.
Propagation speed 82%
Impedance 75 Ohm
Nom. Delay 4.0 ns / m.
Operating temperature -30 / + 70 °C
Attenuation dB / 100m:
10 MHz 2.03
100 MHz 6.71
1000 MHz 20.00
2000 MHz 29.00
3000 MHz 36.00
4500 MHz 46.00
RoHS2 Compliant: Ver. A / 16.05.16