MULTICOAXIAL VIDEO CABLE 5X0.08 (75) BLACK 100MT



Multi Mini special coaxial video cable - 5x0.08 mm (75 Ohm)
For applications in video transmission systems and professional monitors.

Référence C145

Black fireproof PVC sheath. External diameter 9,20 (ñ 0,20) mm.
Grouping with non-woven polyester tape.
Soft PVC sheath on single conductors. Diam. 2.40 (ñ 0.20) mm.
Colorful: Red, Green, Blue, Black and White.
O.F.C. tinned copper braid shield which covers 90%.
Core insulation with PPE - Diam. 1.40 (ñ 0.20) mm.
O.F.C. tinned copper braid formation, 7x0.12 mm.
Nom. Section 5x0.08 mmý (75Ohm).
Ownership:
Conductor resistance 203 Ohm / Km
Core / Screen Capacity 67 pF / mt
Propagation speed 66%
Impedance 75 Ohm
Maximum rated voltage 49 V
Operating temperature -20 / + 70 ø C
Attenuation dB / 100 mt:
50 MHz 19.70
100 MHz 28.70
200 MHz 42.00
400 MHz 61.20
800 MHz 88.50
1000 MHz 105.00
RoHS3 Compliant: Ver. A / 07.12.2015