CABLE S-VGA-XGA 5X0.08 (75) + 5X0.08 BLACK 100MT

Special 75Ohm video cable
For VGA and XGA applications

Référence C146



Black flame retardant soft PVC.
External diameter 9.00 (ñ 0.20) mm.
O.F.C. O.F.C. tinned copper braid shield, 80% coverage + drain wire.
Grouping with non-woven polyester tape.
Coaxial video:
PVC sheath. Colored: Red, Green, Blue, White, Black.
Diam. 2.40 (ñ 0.20) mm.
O.F.C. tinned copper spiral shield, 100% coverage.
PPE insulated. Diam.1,40 (ñ 0,20) mm.
Tinned copper strands O.F.C. 7x0.12 mm.
Nominal section 5x0.08 mmý (75Ohm).
Isolated nuclei:
PVC sheath. Colored: White, brown, red, orange, yellow.
Diam.0.90 (ñ 0.20) mm.
O.F.C. tinned copper strand formation 7x0.12 mm.
Nom. Section 5x0.08 mmý.
Ownership:
Conductors Resistance 203 Ohm / Km
Impedence 75 Ohm
Velocity of Propagation 66%
Capacity Core / Shield 67 pF / m
Operating temperatures -20 / + 70 ø C
Attenuation dB / 100 m:
50 MHz 19.70
100 MHz 28.70
200 MHz 42.00
400 MHz 61.20
800 MHz 88.50
1000 MHz 105.00
RoHS3 Compliant: Ver. A / 16.05.17