
KOMBY CABLE -1 VIDEO + SWITCH 1X0.08 (75) + 2X0.50 BLACK 100 MT

Special video cable - 1x0.08
(75Ohm) + 2x0.50 mm
For video security, security
and camcorder applications.

Référence C226



Black flame retardant soft PVC sheath.

External cable Diam. 6.60 (ñ 0.20) mm.

75 Ohm Video Coax:

Internal sheath in fireproof PVC.

Diam. 2.80 (ñ 0.20) mm.

Spiral shield in tinned copper O.F.C. 100% coverage.

Dielectric in white PEE. Diam. 1.50 (ñ 0.20) mm.

Formation of red copper O.F.C. stranded 10x0.10 mm.

Nom. Section 1x0.08 mm²

Isolated nuclei:

Internal sheaths in fireproof PVC.

Both black in color. Diam. 1.90 (ñ 0.20) mm.

16x0.20 mm stranded formations, one conductor in tinned copper O.F.C. and one in red copper. Nom. Section 2x0.50 mm².

Ownership:

Insulated Conductors Resistance 38.00 Ohm / Km

Coax Conductor Resistance 203 Ohm / Km

Coax Capacity Core / Shield 67 pF / m

Coax Velocity of Propagation 66%

Coax Impedance 75 Ohm

Max Rated Voltage 49V

Operating temperatures -20 / + 70 °C

Coaxial Properties Attenuation dB / 100 m:

50 MHz 19.50

100 MHz 28.50

200 MHz 41.70

400 MHz 60.20

800 MHz 87.30

1000 MHz 103.00

RoHS2 Compliant: Ver. B / 26.05.19