KOMBY CABLE -1 VIDEO + SWITCH 1X0.26 (75) + 2X0.50 WHITE 100 MT



Special video cable - 1x75Ohm + 2x0.50mm
For general video and video surveillance applications.

Référence C227

White fireproof soft PVC sheath.
External cable Dimensions 8.00 (ñ 0.20) mm.
75 Ohm Video
White fireproof PVC sheath.
Diameter 4.10 (ñ 0.20) mm.
O.F.C.red copper braid shield Coverage 85%.
White PPE insulation. Diameter 2.70 (ñ 0.20) mm.
O.F.C. red copper red rigid wire formation 1x0.58 mm.
Nom. Section 1x0.26 mmý
Isolated nuclei
Sheaths in fireproof PVC. Colored one black and one red.
Diameter 2.10 (ñ 0.20) mm.
16x0.20 mm strand formation in OFC red copper.
Nom. Section 2x0.50 mmý.
Ownership:
Free Conductors Resistance 38 Ohm / Km
Coax Conductor Resistance 75 Ohm / Km
Coax Capacity Core / Shield 67 pF / mt
Coax Impedance 75 Ohm
Max Rated Voltage 49V
Operating temperatures -20 / + 70 ø C
Attenuation dB / 100 m:
50 MHz 17.2
100 MHz 24.6
200 MHz 33.7
400 MHz 40.5
800 MHz 65.5
1000 MHz 87.2