BAND KOMBY 1 VIDEO + 2 AUDIO 1X0.08 (75) + 2X0.14 BLACK 100 MT



Special divisible flat video cable - 1x0.08 (75Ohm) + 2x0.14 mm
For audio / video applications

Référence C228

Black soft PVC sheath.
External dimensions: 3.40x10.40 (ñ 0.20) mm.
Audio section:
O.F.C.red copper spiral shield, 100% coverage.
PVC insulation, colored one red and one white.
Diam. 1.50 (ñ 0.20) mm.
Red copper stranded formation O.F.C. 18x0.10 mm.
Nom. Section 2x0.14 mmý.
Video section:
O.F.C. tinned copper spiral shield, 100% coverage.
Insulation with yellow PEE. Diam. 1.50 (ñ 0.20) mm.
Formation of red copper O.F.C. stranded 10x0.10 mm.
Nom. Cross section 1x0.08 mmý (75Ohm)
Audio Properties:
Conductor resistance 138 Ohm / Km
Core / Core capacity 50 pF / m
Core / Shield capacity 250 pF / m
Video Properties:
Conductor Resistance 203 Ohm / Km
Impedence 75 Ohm
Velocity of Propagation 66%
Capacity Core / Shield 67 pF / m
General properties:
Maximum rated voltage 49 V
Operating temperature -15 / + 70 ø C
Attenuation dB / 100 mt:
50 MHz 19.5
100 MHz 28.5
200 MHz 41.7
400 MHz 60.2
800 MHz 87.3
1000 MHz 103.0
RoHS2 Compliant: Ver. A / 26.05.17