MULTICOAXIAL CABLE -VIDEO + SWITCH 5X0.08 (75) + 4X0.22 BLACK 100 MT



Super special 75Ohm video cable
APPLICATIONS RGB video + command / switch

Référence C263SUPER

Gray soft flame retardant PVC.
External diameter 10.00 (ñ 0.20) mm.
5x Coax Video:
PVC sheath. Colored: Red, Green, Blue, Black, White.
Diam. 2.80 (ñ 0.20) mm.
O.F.C. tinned copper spiral shield, 100% coverage.
PEE insulated. Diam. 1.60 (ñ 0.20) mm.
Tinned copper strands O.F.C. 10x0.10 mm.
Nominal section 5x0.08 mmý (75Ohm).
4x Isolated nuclei:
PVC sheath. Colored: Yellow, Brown, Gray, Purple.
Diam. 1.20 (ñ 0.20) mm.
O.F.C. tinned copper strand formation 7x0.20 mm.
Nominal section 4x0.22 mmý.
Ownership:
Coax Conductors Resistance 203 Ohm / Km
Impedence 75 Ohm
Velocity of Propagation 66%
Capacity Core / Shield 67 pF / m
Free Conductors Resistance 79.15 Ohm / Km
Operating temperatures -20 / + 70 ø C
Attenuation dB / 100 m:
50 MHz 19.50
100 MHz 28.50
200 MHz 41.70
400 MHz 60.20
800 MHz 87.30
1000 MHz 103.00
RoHS2 Compliant: Ver. A / 16.05.17