

---

# MULTICUPLE AUDIO CABLE 52X2X0,22 BLACK 100 MT

Individually shielded  
multipair audio cable -  
52x2x0.22 mm<sup>2</sup>  
For wiring audio mixers,  
banks and balanced audio  
patches.

Référence C452



Black soft PVC sheath.

External cable Diam. 8.00 (ñ 0.20) mm.

The individual pairs are insulated with black PVC, numbered from one to the number of elements and wrapped together with polyester base tape. Nom. 3.00 (ñ 0.20) mm.

The single pairs are shielded with O.F.C. red copper spiral, 100% coverage + tinned copper drain wire.

Individual cores are insulated with solid PE, colored one yellow and one clear, and wrapped with non-woven polyester base tape.

Nom. 1.00 (ñ 0.20) mm.

Formation of red copper O.F.C. 28x0.10 mm. Nom. Section 52x2x0.22 mm<sup>2</sup>.

Ownership:

Conductor resistance: 79.15 Ohm / Km

Core / Core capacity: 75 pF / m

Core / Screen Capacity: 160 pF / m

Propagation Rate: 66%

Maximum rated voltage: 49V

Operating temperature: -15 / + 70 ° C

RoHS3 Compliant: Ver. B / 24.06.19