
KOMBY CABLE CAT 6A + POWER LSZH 2X (4X2X0.25) + 3X2.50 BLACK 100 MT

Combined cable 2x Cat.6A
F./F.T.P. LAN + 3x1.50 mm²
For broadcast, DMX and LAN
network cabling applications

Référence C735LSHZ



Black sheath L.S.Z.H. - Fire resistant and halogen free.

External cable Size 20.00 (ñ 0.20) mm.

The internal elements are woven with polyester-based ribbon

3x1.50 mm² Power conductors:

Inner sheath L.S.Z.H. Black. Fire resistant and halogen free. Diam. 7.00 (ñ 0.20) mm.

Conductor insulation with L.S.Z.H. - Fire resistant and halogen free. Colored Brown, Blue and Yellow / Green. Diam. 2.30 (ñ 0.20) mm.

28x0.25 mm strand formation in O.F.C. Nom. Cross section 3x1.50 mm².

2x (4x2x0.25) mm² LAN cable Cat.:6A F./F.T.P. .:

Black inner sheath in L.S.Z.H. fire resistant and halogen free.

Diam. 7.60 (ñ 0.20) mm.

Total shielding with aluminum foil tape covering 100%. + Drainage wire and total taping of the pairs.

The four pairs are individually shielded with aluminum foil tape covering 100%.

PEE conductor insulation, stranded in pairs.

Diam.1.40 (ñ 0.10) mm.

Color code: White / Blue, White / Orange, White / Green, White / Brown.

O.F.C. Red Copper Red Formation rigid copper wire of 1x0.57 mm. Nom. Section 4x2x0.25 mm².

Ownership:

Power conductor resistance: 6.41 Ohm / Km

Cat.6A Conductor resistance: 75.85 Ohm / Km

Minimum bend radius: 10x O.D.

Maximum pulling force: 320N

Maximum rated voltage: 49V

Operating temperature: -25 / + 75 ø C

RoHS2 Compliant: Ver. A / 26.05.17