COAX MIL STANDARD CABLE 1X0.05 (75) TRANSPARENT 100 MT

RG 179 U - Mil. C 17 Coaxial cable 75 Ohm Standard - 1x0,05 mm2
For mini coaxial connections and video signals

Référence RG179U



Transparent sheath in Fluorinated Ethylene Propylene (FEP Teflon).
Self-extinguishing flame retardant (IEC 60332-1-2), halogen, UV, water, chemical, solvent free and oil resistant.
Specifically designed for high or low temperatures even for outdoor applications.
Diam. 2.54 (ñ 0.10) mm.
O.F.C. with 95% coverage.
Core insulation with transparent fluorinated ethylene propylene
(FEP Teflon) - Diam. 1,58 (ñ 0,20) mm.
CW silver plated strand formation 7x0.10 mm.
Nom. Cross section 1x0.05 mm2
Ownership:
Conductor resistance: 800 Ohm / Km
Core / Screen Capacity: 64 pF / m
Propagation Rate: 69%
Impedance: 75 Ohm
Operating temperature: -60 / + 200 ø C
Attenuation db / 10m:
50 MHz - 2.80
100 MHz - 3.30
400 MHz - 5.30
700 MHz - 6.50
1000 MHz - 7.90

RoHS2 Compliant: Ver. A / 16.05.16