

---

# COAX HDTV - HD SDI CABLE 23 AWG Ø 4.0 MM BLACK 100 MT

HD SDI - 75 Ohm coaxial  
cable - 1x0.28 mm  
APPLICATIONS Digital video  
for high definition video  
transmission and installation

Référence TSK1077LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.  
Limited application outside. External diameter. 4.20 (ñ 0.20) mm.  
First O.F.C. tinned copper covering 95% of the braid.  
Second shield in aluminum tape, 100% coverage.  
Core insulation with PE foam. Diam. 2.80 (ñ 0.20) mm.  
Formation of rigid wire 1x0.60 mm in red copper O.F.C.  
Nom. Section 1x0.26 mm<sup>2</sup>.  
Ownership:  
Conductor resistance 62 Ohm / Km  
Core / Screen Capacity 53.5 pF / m.  
Propagation speed 82%  
Impedance 75 Ohm  
Nom. Delay 4.0 ns / m.  
Operating temperature -30 / + 70 °C  
Attenuation dB / 100m:  
10 MHz 3.31  
100 MHz 11.80  
1000 MHz 38.07  
2000 MHz 54.48  
3000 MHz 69.47  
4500 MHz 88.89  
RoHS2 Compliant: Ver. A / 16.05.16