

---

# COAX HDTV - HD SDI CABLE 20 AWG Ø 5.9 MM BLACK 100 MT

HD SDI - 75 Ohm coaxial  
cable - 1x0.52 mm  
APPLICATIONS Digital video  
for high definition video  
transmission and installation

Référence TSK1078LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.  
Limited application outside. External diameter. 6.00 (ñ 0.20) mm.  
First O.F.C. tinned copper covering 95% of the braid.  
Second shield in aluminum tape, 100% coverage.  
Core insulation with PE foam. Diam. 3.50 (ñ 0.20) mm.  
Formation of rigid wire 1x0.80 mm in red copper O.F.C.  
Nom. Section 1x0.50 mm<sup>2</sup>.  
Ownership:  
Conductor resistance 38 Ohm / Km  
Core / Screen Capacity 53.5 pF / m.  
Propagation speed 82%  
Impedance 75 Ohm  
Nom. Delay 4.0 ns / m.  
Operating temperature -30 / + 70 °C  
Attenuation dB / 100m:  
10 MHz 2.03  
100 MHz 7.31  
1000 MHz 24.60  
2000 MHz 36.74  
3000 MHz 50.11  
4500 MHz 67.64  
RoHS2 Compliant: Ver. A / 16.05.16