
COAX HDTV - HD SDI CABLE 18 AWG Ø 7.0 MM BLACK 100 MT

3G - SDI - 75 Ohm coaxial
cable - 1x0.80 mm
APPLICATIONS Digital video
for high definition video
transmission and installation

Référence TSK1079LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.
Limited application outside. External diameter. 7.00 (ñ 0.20) mm.
First O.F.C. tinned copper covering 95% of the braid.
Second shield in aluminum tape, 100% coverage.
Core insulation with PE foam. Diam. 4.60 (ñ 0.20) mm.
Formation of rigid wire 1x1,00 mm in red copper O.F.C.
Nom. Section 1x0.80 mm².
Ownership:
Conductor resistance 21 Ohm / Km
Core / Screen Capacity 53.5 pF / m.
Propagation speed 82%
Impedance 75 Ohm
Nom. Delay 4.0 ns / m.
Operating temperature -30 / + 70 °C
Attenuation dB / 100m:
10 MHz 2.03
100 MHz 6.71
1000 MHz 20.00
2000 MHz 29.00
3000 MHz 36.00
4500 MHz 46.00
RoHS2 Compliant: Ver. A / 16.05.16