
COAX HDTV - HD SDI CABLE 14 AWG Ø 10.2 MM BLACK 100 MT

3G - SDI - 75 Ohm coaxial
cable - 1x2.00 mm
APPLICATIONS Digital video
for high definition video
transmission and installation

Référence TSK1080LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.
Limited application outside. External diameter. 10.20 (ñ 0.20) mm.
First O.F.C. tinned copper covering 95% of the braid.
Second shield in aluminum tape, 100% coverage.
Core insulation with PE foam. Diam.7.10 (ñ 0.20) mm.
Formation of rigid wire 1x1.60 mm in red copper O.F.C.
Nom. Section 1x2.00 mmý.
Ownership:
Conductor resistance 5.10 Ohm / Km
Core / Screen Capacity 52.5 pF / m.
Propagation speed 85%
Impedance 75 Ohm
Nom. Delay 4.0 ns / m.
Operating temperature -30 / + 70 ø C
Attenuation dB / 100m:
1 MHz 0.62
10 MHz 1.39
100 MHz 4.73
1000 MHz 16.50
2000 MHz 26.53
3000 MHz 34.77
4500 MHz 43.98
RoHS2 Compliant: Ver. B / 08.05.19