
4x4 4K HDMI SEAMLESS MATRIX PROCR CON SCALER 4X4

4x4 4K 18Gbps Seamless
HDMI Matrix Switcher/Video
Wall Processor/Multiviewer
with Scaler/IR/Audio/IP and
RS-232



Reference: BG-4K-VP44

SWITCHER/PROCESSOR/VIDEOWALL/MULTIVIEWER

HDMI Matrix 4X4 4K 18 Gbps seamless/Video Wall Processor/Multiviewer with Scaler/IR/Audio/IP and RS-232

The BG-4K-VP44 supports eight HDMI inputs which can be independently routed to HDMI outputs. This unit can create video walls, act as a multi-viewer and perform matrix functions! The BG-4K-VP88 supports video wall configurations of up to 7 different modes with each monitor. It can also display eight images on the same screen and has multiple split display modes.

With maximum resolutions up to 4K@60Hz 4:4:4, the BG-4K-VP44 is capable of producing high-quality images with sharp detail and rich colors. All HDMI ports on this unit are HDCP 2.2 compliant. This device also supports analog audio extraction, and the audio channels can be switched independently.

The BG-4K-VP44 offers multiple control methods, including front panel controls, IR remote control, RS-232 or IP control. The included IR receiver allows you to control the unit with the included remote while placed out of sight for a clean install.

In addition to a comprehensive web interface, the BG-4K-VP44 includes control software that can be operated via the RS-232 connection. These interfaces allow users to adjust advanced features such as EDID management, mapping and network settings.

Technical specifications

- 4xHDMI input ports
- 4xHDMI output ports
- Supported video format 4K@60Hz , YUV4:4:4 8 bit
- 4K@30Hz /1080P/1080i/720P
- Supported Audio Formats DTS-5.1/Dolby-5.1 HDMI Digital Audio
- HDCP 2.2 and HDCP 1.4 compliant
- 0.5-1.0 volt pp video signal input
- DDC 5 volt pp (TTL) signal input
- 18 Gbit/sec bandwidth
- Matrix Mode 8x8 Continuous Switching
- Video Wall Mode Multiple video wall modes
- Multi-Viewer Mode Multiple Multi-Viewer Modes
- Power consumption 23 Watts (maximum)
- Operating temperature range from -5 to +40°C

-
- Storage temperature range -14 to +140°F / -10 to +60°C
 - Operating Humidity Range 5 to 90% RH (non-condensing)
 - Die Dimensions: 10"(L) x 6.4"(W) x 1.4"(H) [L262 x W163 x H36mm]

Do you want more information about it?

[Contact us now!](#)