FLAME THROWER WITH 5 HEADS, GENERATES FLAMES FROM 8 TO 10 METERS



5-HEAD FLAME THROWER, GENERATES FLAMES FROM 8 TO 10 METERS

Reference: F5

5-HEAD FLAME THROWER, GENERATES FLAMES FROM 8 TO 10 METERS

Equipped with 5 nozzles and 97 pre-set firing sequences, the F5 offers independent control of each nozzle, ensuring a flawless and safe flame experience.

With an 80° angle and a fuel level indicator, this machine is designed to provide you with maximum control and ease of use.

Technical Specifications

- Range Angle: 80 degrees
- 5 nozzles
- Voltage: AC 110V & 220V 50/60Hz
- Power: 2200 W
- Flame Height: 8 10 meters (without wind)
- Independent control of each nozzle
- Range Angle: 80 degrees (-40 -20 -0 +20 +40)
- · Fuel Type: Isopar
- Fuel Tank Capacity: 34 L
- Fuel Consumption: 60ml/s per nozzle
- Solenoid Valve for Fuel Volume Control
- Firing Sequence: 97 pre-set firing sequences
- Work Channel: 6 channels
- Independent Nozzle Control
- Control: DMX 512
- Double Ignition per Nozzle
- Double Pump per Nozzle
- Operating Temperature: -20°C / 50°C
- Machine Weight: 90 Kg
- Machine Dimensions: 612 × 543 × 604 mm
- Weight with Packaging: 111 Kg
- Dimensions with flightcase without wheels (L x H x W): 730 x 690 x 670 mm
- Certifications: CE RoHS
- · Case Material: Stainless Steel 304

Do you want more information about our product?

Contact us now!