
BAND KOMBY 1 VIDEO + 2 AUDIO 1X0.08 (75) + 2X0.14 BLACK 100 MT

Special divisible flat video cable - 1x0.08 (75Ohm) + 2x0.14 mm
For audio / video applications

Reference: C228



Black soft PVC sheath.

External dimensions: 3.40x10.40 (ñ 0.20) mm.

Audio section:

O.F.C. red copper spiral shield, 100% coverage.

PVC insulation, colored one red and one white.

Diam. 1.50 (ñ 0.20) mm.

Red copper stranded formation O.F.C. 18x0.10 mm.

Nom. Section 2x0.14 mm².

Video section:

O.F.C. tinned copper spiral shield, 100% coverage.

Insulation with yellow PEE. Diam. 1.50 (ñ 0.20) mm.

Formation of red copper O.F.C. stranded 10x0.10 mm.

Nom. Cross section 1x0.08 mm² (75Ohm)

Audio Properties:

Conductor resistance 138 Ohm / Km

Core / Core capacity 50 pF / m

Core / Shield capacity 250 pF / m

Video Properties:

Conductor Resistance 203 Ohm / Km

Impedence 75 Ohm

Velocity of Propagation 66%

Capacity Core / Shield 67 pF / m

General properties:

Maximum rated voltage 49 V

Operating temperature -15 / + 70 °C

Attenuation dB / 100 mt:

50 MHz 19.5

100 MHz 28.5

200 MHz 41.7

400 MHz 60.2

800 MHz 87.3

1000 MHz 103.0

RoHS2 Compliant: Ver. A / 26.05.17