KOMBY VIDEO CABLE FOR SECURITY 1X0.58 (75) + 2X0.75 WHITE 100 MT



Special video cable - 1x75Ohm + 2x0.75mm
For video surveillance and camera cabling applications.

Reference: C230

Flame retardant soft PVC sheath. White color.
External cable Diameter 10.50 (ñ 0.20) mm.
75 Ohm Video
Sheath in fireproof PVC. White color.
Diameter 6.20 (ñ 0.20) mm.
O.F.C.red copper braid shield Coverage 98%.
Transparent compact PE insulation.
Diameter 3.70 (ñ 0.20) mm.
Rigid wire CW 1x0.58 mm.
Nom. Cross section 1x0.26 mmý.
Isolated nuclei
Sheaths in fireproof PVC, colored one black and one red.
Diameter 1.90 (ñ 0.20) mm.
24x0.20 mm strand formation in OFC red copper
Nom. Cross section 2x0.75 mmý.
Coaxial properties:
Resistance of insulated conductors 21.93 Ohm / Km
Resistance of the coaxial conductor 158 Ohm / Km
Core / Screen coaxial capacitance 67 pF / m
75 Ohm coaxial impedance
Maximum rated voltage 49V
Operating temperature -20 / + 70 ø C
Attenuation dB / 100 m:
50 MHz 7.40
100 MHz 10.70
200 MHz 15.70
400 MHz 22.70
800 MHz 33.60
1000 MHz 38.00
RoHS2 Compliant: Ver. A / 16.05.17