
VGA CABLE 3X0.08 (75) + 7X0.08 GRAY 100MT

Special video cable -
3x75Ohm + 7x0.08 mm
For making VGA and XGA
cables.

Reference: C258



Gray soft flame retardant PVC.
External diameter 7.60 (ñ 0.20) mm.
O.F.C. O.F.C. tinned copper braid shield, 80% coverage + drain wire.
Grouping with non-woven polyester tape.
3x HD Coax Video:
105 ø HT PVC sheath - Colored: Red, Green and Blue.
Diam. 2.40 (ñ 0.20) mm.
O.F.C. O.F.C. tinned copper spiral shield, 100% coverage.
PPE insulated. Diam.1,40 (ñ 0,20) mm.
Tinned copper strands O.F.C. 7x0.12 mm.
Nominal section 3x0.08 mmý (75Ohm).
7x Isolated nuclei:
Sheath in PVC HT 105 ø - Colored: White, Brown, Red, Orange, Yellow,
Green Black. Diam.0.90 (ñ 0.20) mm.
O.F.C. tinned copper strand 7x0.12 mm.
Nominal section 7x0.08 mmý.
Ownership:
Conductors Resistance 203 Ohm / Km
Impedence 75 Ohm
Velocity of Propagation 66%
Capacity Core / Shield 67 pF / m
Operating temperatures -20 / + 70 ø C
Attenuation dB / 100 m:
50 MHz 19.70
100 MHz 28.70
200 MHz 42.00
400 MHz 61.20
800 MHz 88.50
1000 MHz 105.00
RoHS2 Compliant: Ver. A / 16.05.17