

---

# MULTICOUPLE DIGITAL AUDIO CABLE 16X2X0.22 BLACK 100 MT

AES / EBU 110 Ohm digital  
audio multipair cable -  
16x2x0.22 mm<sup>2</sup>  
For applications in digital  
audio and DMX cabling

Reference: C816



Soft sheath in black fireproof PVC. External cable Diam. 22,30 (ñ 0,20) mm.

The pairs are wrapped together with polyester base tape.

The single pairs are insulated with black fireproof PVC, numbered from one to the number of elements. Diam.4.00 (ñ 0.20) mm.

The single pairs are shielded with O.F.C.red copper spiral. covering 100% + tinned copper drain wire.

Individual cores are isolated with DPI, colored one blue and one red. Diam. 1.50 (ñ 0.20) mm.

Formation of tinned copper O.F.C. 28x0.10 mm. Nom. Section 16x2x0.22mm<sup>2</sup>

Ownership:

Conductor resistance: 79.15 Ohm / Km

Core / Core capacity: 50 pF / m

Core / Screen Capacity: 95 pF / m

Impedance: 110 Ohm

Maximum rated voltage: 49V

Operating temperature: -15 / + 70 ø C

RoHS3 Compliant: Ver. B / 16.05.19