
COAX MIL STANDARD CABLE 1X0.05 (75) TRANSPARENT 100 MT

RG 179 U - Mil. C 17 Coaxial
cable 75 Ohm Standard -
1x0,05 mm²

For mini coaxial connections
and video signals

Reference: RG179U



Transparent sheath in Fluorinated Ethylene Propylene (FEP Teflon).

Self-extinguishing flame retardant (IEC 60332-1-2), halogen, UV, water, chemical, solvent free and oil resistant. Specifically designed for high or low temperatures even for outdoor applications.

Diam. 2.54 (ñ 0.10) mm.

O.F.C. with 95% coverage.

Core insulation with transparent fluorinated ethylene propylene (FEP Teflon) - Diam. 1,58 (ñ 0,20) mm.

CW silver plated strand formation 7x0.10 mm.

Nom. Cross section 1x0.05 mm²

Ownership:

Conductor resistance: 800 Ohm / Km

Core / Screen Capacity: 64 pF / m

Propagation Rate: 69%

Impedance: 75 Ohm

Operating temperature: -60 / + 200 ø C

Attenuation db / 10m:

50 MHz - 2.80

100 MHz - 3.30

400 MHz - 5.30

700 MHz - 6.50

1000 MHz - 7.90

RoHS2 Compliant: Ver. A / 16.05.16