

---

# COAX HDTV - HD SDI CABLE 23 AWG Ø 4.0 MM BLACK 100 MT

HD SDI - 75 Ohm coaxial  
cable - 1x0.28 mm  
APPLICATIONS Digital video  
for high definition video  
transmission and installation

Reference: TSK1077LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.  
Limited application outside. External diameter. 4.20 (ñ 0.20) mm.  
First O.F.C. tinned copper covering 95% of the braid.  
Second shield in aluminum tape, 100% coverage.  
Core insulation with PE foam. Diam. 2.80 (ñ 0.20) mm.  
Formation of rigid wire 1x0.60 mm in red copper O.F.C.  
Nom. Section 1x0.26 mm<sup>2</sup>.  
Ownership:  
Conductor resistance 62 Ohm / Km  
Core / Screen Capacity 53.5 pF / m.  
Propagation speed 82%  
Impedance 75 Ohm  
Nom. Delay 4.0 ns / m.  
Operating temperature -30 / + 70 °C  
Attenuation dB / 100m:  
10 MHz 3.31  
100 MHz 11.80  
1000 MHz 38.07  
2000 MHz 54.48  
3000 MHz 69.47  
4500 MHz 88.89  
RoHS2 Compliant: Ver. A / 16.05.16