COAX HDTV - HD SDI CABLE 14 AWG Ø 10.2 MM BLACK 100 MT



3G - SDI - 75 Ohm coaxial cable - 1x2.00 mm
APPLICATIONS Digital video for high definition video transmission and installation

Reference: TSK1080LSHZ

L.S.Z.H. dark blue sheath. Flame retardant and halogen free.
Limited application outside. External diameter. 10.20 (ñ 0.20) mm.
First O.F.C. tinned copper covering 95% of the braid.
Second shield in aluminum tape, 100% coverage.
Core insulation with PE foam. Diam.7.10 (ñ 0.20) mm.
Formation of rigid wire 1x1.60 mm in red copper O.F.C.
Nom. Section 1x2.00 mmý.
Ownership:
Conductor resistance 5.10 Ohm / Km
Core / Screen Capacity 52.5 pF / m.
Propagation speed 85%
Impedance 75 Ohm
Nom. Delay 4.0 ns / m.
Operating temperature -30 / + 70 ø C
Attenuation dB / 100m:
1 MHz 0.62
10 MHz 1.39
100 MHz 4.73
1000 MHz 16.50
2000 MHz 26.53
3000 MHz 34.77
4500 MHz 43.98
RoHS2 Compliant: Ver. B / 08.05.19