
DIGITAL AUDIO CABLE 1X2X0.22 BLACK 100 MT

Digital Audio Cable with
double shielding 110 Ohm
AES / EBU - 2x0.22 mm²

For digital audio and DMX
cabling applications

Reference: CZZDMX801



Digital Audio / DMX Cable on a 100m Reel

Black soft PVC sheath. External cable diameter \varnothing 6.20 (\pm 0.10) mm. Second soft PVC sheath - diameter \varnothing 4.40 (\pm 0.10) mm.

O.F.C. Shielding Red Copper 100% Copper Spiral Spiral. + Tinned O.F.C. copper drain wire.

Core insulation with DPI, one red and one blue. The conductors are wrapped together with recycled textile filling material.

Diameter \varnothing 1.50 mm (\pm 0.10) mm. Tinned O.F.C. copper formation 28x0.10 mm. Nom. Section 2x0.22 mm²

Features:

- Conductor Resistance: 79.15 Ω /Km
- Core/Core Capacitance: 50 pF/m
- Core/Shield Capacitance: 95 pF/m
- Impedance: 110 Ω
- Maximum Rated Voltage: 49 V
- Operating Temperature: -15/+70°C
- RoHS3 Compliant: Ver. B / 16.05.19

Do you want more information about our product?

[Contact us now!](#)