DIGITAL CABLE DMX AUDIO + POWER 2X2X0,22 + 3X1,50 BLACK 100 MT



Special DMX cable 110 Ohm - 2x2x0.22 + 3x1.50 mm2
For the construction of digital audio cables.

Reference: C284

Black fireproof PVC. External cable Diam. 13.80 (ñ 0.20) mm.
The single sheath is coupled with a filler material between the conductors all wrapped with non-woven polyester tape.
Digital torque 110 Ohm:
Black fireproof PVC. Diam.4.00 (ñ 0.20) mm. O.F.C. red copper 100% spiral cover + O.F.C. tinned copper Tinned copper drain wire.
Core insulation with PEE, colored one red and one blue.
Diam. 1.50 (ñ 0.20) mm.
Tinned copper O.F.C. - formation 28x0,10 mm. Nom. Section 1x2x0.22 mm.
Three power conductors:
Black fireproof PVC. Diam.7.20 (ñ 0.20) mm. Insulation core with colored flame retardant PVC:
Brown, Blue and Yellow / Green. Diam. 3.00 (ñ 0.20) mm. Formation of red copper O.F.C. 48x0.20 mm.
Nom. Cross section 3x1.50 mm2.
Ownership:
Resistance of digital audio cables: 79.15 Ohm / Km
Digital Audio Impedance: 110 Ohm
Power conductor resistance: 12.50 Ohm / Km
Core / Core capacity: 50 pF / mt
Core / Screen Capacity: 89 pF / mt
Maximum rated voltage: 49V
Operating temperature: -20 / + 70 ø C
RoHS2 Compliant: Ver. A / 16.05.16