KOMBY CABLE CAT 6A + POWER LSZH 2X (4X2X0.25) + 3X2.50 BLACK 100 MT



Combined cable 2x Cat.6A F./F.T.P. LAN + 3x1.50 mm2
For broadcast, DMX and LAN network cabling applications

Reference: C735LSHZ

Black sheath L.S.Z.H. - Fire resistant and halogen free.
External cable Size 20.00 (ñ 0.20) mm.
The internal elements are woven with polyester-based ribbon
3x1.50 mm2 Power conductors:
Inner sheath L.S.Z.H. Black. Fire resistant and halogen free. Diam. 7.00 (ñ 0.20) mm.
Conductor insulation with L.S.Z.H. - Fire resistant and halogen free. Colored Brown, Blue and Yellow / Green. Diam. 2.30 (ñ 0.20) mm.
28x0.25 mm strand formation in O.F.C. Nom. Cross section 3x1.50 mm2.
2x (4x2x0.25) mm2 LAN cable Cat.:6A F./F.T.P .:
Black inner sheath in L.S.Z.H. fire resistant and halogen free.
Diam. 7.60 (ñ 0.20) mm.
Total shielding with aluminum foil tape covering 100%. + Drainage wire and total taping of the pairs.
The four pairs are individually shielded with aluminum foil tape covering 100%.
PEE conductor insulation, stranded in pairs.
Diam.1.40 (ñ 0.10) mm.
Color code: White / Blue, White / Orange, White / Green, White / Brown.
O.F.C. Red Copper Red Formation rigid copper wire of 1x0.57 mm. Nom. Section 4x2x0.25 mm2.
Ownership:
Power conductor resistance: 6.41 Ohm / Km
Cat.6A Conductor resistance: 75.85 Ohm / Km
Minimum bend radius: 10x O.D.
Maximum pulling force: 320N
Maximum rated voltage: 49V
Operating temperature: -25 / + 75 ø C
RoHS2 Compliant: Ver. A / 26.05.17