

---

# COAX HDTV - HD SDI CABLE 14 AWG Ø 10.2 MM BLACK 100 MT

3G - SDI - 75 Ohm coaxial  
cable - 1x2.00 mm  
APPLICATIONS Digital video  
for high definition video  
transmission and installation

Reference: TSK1080LSHZ



L.S.Z.H. dark blue sheath. Flame retardant and halogen free.  
Limited application outside. External diameter. 10.20 (ñ 0.20) mm.  
First O.F.C. tinned copper covering 95% of the braid.  
Second shield in aluminum tape, 100% coverage.  
Core insulation with PE foam. Diam.7.10 (ñ 0.20) mm.  
Formation of rigid wire 1x1.60 mm in red copper O.F.C.  
Nom. Section 1x2.00 mmý.  
Ownership:  
Conductor resistance 5.10 Ohm / Km  
Core / Screen Capacity 52.5 pF / m.  
Propagation speed 85%  
Impedance 75 Ohm  
Nom. Delay 4.0 ns / m.  
Operating temperature -30 / + 70 ø C  
Attenuation dB / 100m:  
1 MHz 0.62  
10 MHz 1.39  
100 MHz 4.73  
1000 MHz 16.50  
2000 MHz 26.53  
3000 MHz 34.77  
4500 MHz 43.98  
RoHS2 Compliant: Ver. B / 08.05.19