

---

# MULTICUPLE DIGITAL AUDIO CABLE 24X2X0.14 BLACK 100 MT

Digital audio multipair cable  
110 Ohm AES / EBU -  
24x2x0.14 mm  
APPLICATIONS Audio mixers,  
banks and balanced audio  
patches

Reference: TSK824



Black soft PVC sheath.

external cable: 22.70 (ñ 0.10) mm.

Individual pairs are insulated with black PVC, individually numbered and wrapped together with polyester base tape.

Diam. 3.20 (ñ 0.10) mm.

Individual pairs are shielded with aluminum tape covering 100% +  
tinned copper drain wire.

The individual cores are insulated with PE foam, colored one white and one red,  
and wrapped with non-woven polyester base tape.

Diam. 1.20 (ñ 0.10) mm.

Formation of tinned copper O.F.C. 18x0.10 mm.

Nom. Section 24x2x0.14 mm<sup>2</sup>.

Ownership:

Conductor Resistance 138.00 Ohm / Km

Capacity Core / Core 50 pF / mt

Capacity Core / Shield 100 pF / mt

Impedance 110 Ohm

Max Rated Voltage 49 V

Operative Temperatures -15 / + 70 °C

RoHS2 Compliant: Ver. A / 16.05.16